

CLASSIFICATION CONFIDENTIAL

CONFIDENTIAL

CENTRAL INTELLIGENCE AGENCY

REPORT

50X1-HUM

INFORMATION FROM

FOREIGN DOCUMENTS OR RADIO BROADCASTS

CD NO.

COUNTRY USSR

DATE OF
INFORMATION 1950

SUBJECT Economic; Technological - Machine tools

HOW
PUBLISHED Monthly periodical

DATE DIST. 12 Sep 1950

WHERE
PUBLISHED Moscow

NO. OF PAGES 1

DATE
PUBLISHED Apr 1950SUPPLEMENT TO
REPORT NO.

LANGUAGE Russian

THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE
OF THE UNITED STATES WITHIN THE MEANING OF ESPIONAGE ACT 80
U. S. C. 31 AND 32, AS AMENDED. ITS TRANSMISSION OR THE REVELATION
OF ITS CONTENTS IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PRO-
HIBITED BY LAW. REPRODUCTION OF THIS FORM IS PROHIBITED.

THIS IS UNEVALUATED INFORMATION

SOURCE Stanki i instrument, No 4, 1950.

HIGH-SPEED WORM THREADING
IN THE USSR

N. V. Ol'khovskiy
V. I. Kapitel'man

High-speed threading of large-size worms (4.5 millimeter module and larger) is done on the DIP-300 screw-cutting lathe with the aid of a special attachment.

The attachment is mounted on the carriage of the machine. It consists of a cutting-tool head with six cutters, a reducing gear, and 2.2 kilowatt electric motor, which are mounted on a common plate. A flange connects the motor with the reducing gear. Movement from the reducing gear to the spindle of the cutting-tool head is transmitted by V-belt drive.

The following conditions of cutting have been established: speed of cutting $v = 225$ meters per minute; feed per revolution of each cutter $s = 0.08-0.15$ millimeters; machining is accomplished in one pass. Rotation of the work piece (the worm) is accomplished by the feed movement.

To achieve the required feed in the kinematic chain of the main movement of the DIP-300 machine, a reducing gear is included which lowers the number of machine tool revolutions 24 times. The kinematic chain in this case is a circular feed of the work piece.

For facilitating the process of cutting, three of the six cutters cut the groove and the other three perform the finishing operation. These cutters are installed in the body of the cutting-tool head in alternating order. The cutters are plated with T15K6 hard alloy. The positive rake of the cutters is 4 degrees.

The cutters will last 3 hours when cutting 20Kh steel, under the above-specified conditions of cutting.

High-speed threading of worms increases labor productivity an average of five times.

- E N D -

- 1 -

CONFIDENTIAL

CLASSIFICATION

CONFIDENTIAL

STATE	<input checked="" type="checkbox"/> NAVY	<input checked="" type="checkbox"/> NSRB	DISTRIBUTION					
ARMY	<input checked="" type="checkbox"/> AIR	<input checked="" type="checkbox"/> FBI						